

| Imperial Inches – Size Group | Outside Diameter mm/Spec Ref | DIN mm | JIS mm | ANSI inches | China Standard (GB) mm |
|------------------------------|------------------------------|--------------|----------------|-------------|------------------------|
| 1/2 | 21.3 mm | 15 | 15 A/21.7 mm | 1/2 | 15*/21.3 mm |
| 3/4 | 26.7 mm | 20/26.9 mm | 20 A/27.2 mm | 3/4 | 20*/26.9 mm |
| 1 | 33.4 mm | 25/33.7 mm | 25 A/34 mm | 1 | 25*/33.7 mm |
| 1 1/4 | 42.2 mm | 32/42.4 mm | 32 A/42.7 mm | 1 1/4 | 32*/42.4 mm |
| 1 1/2 | 48.3 mm | 40 | 40 A/48.6 mm | 1 1/2 | 40*/48.3 mm |
| 2 | 60.3 mm | DN & ISO 50 | 50 A/60.5 mm | 2 | 50*/60.3 mm |
| 2 1/2 | 73.1 mm | — | — | 2 1/2 | — |
| 3 | 76.1 mm DIN/ISO (3 OD) | DN & ISO 65 | 65 A/76.3 mm | — | 65*/76.1 mm |
| | 88.9 mm | DN & ISO 80 | JIS 80 A | 3 | 80*/88.9 mm |
| 4 | 108 mm China and old DIN | DIN 108 mm | — | — | 108 mm |
| | 114.3 mm | DN & ISO 100 | JIS 100 A | 4 | 100*/114.3 mm |
| 5 | 133 mm China and old DIN | DIN 133 mm | — | — | 133 mm |
| | 139.7 mm DIN/ISO (5.5 OD) | DN & ISO 125 | 125 A/139.8 mm | — | 125*/139.7 mm |
| | 141.3 mm | — | — | 5 | — |
| 6 | 159 mm China and old DIN | DIN 159 mm | — | — | 159 mm |
| | 165.1 mm JIS (6.5 OD) | — | 150 A/165.2 mm | — | — |
| | 168.3 mm | DN & ISO 150 | — | 6 | 150*/168.3 mm |
| 8 | 216.3 JIS | — | JIS 200 A | — | — |
| | 219.1 mm | DN 200 | — | 8 | 219.1 mm |
| 10 | 267.4 JIS | — | JIS 250 A | — | — |
| | 273 mm | DN 250 | — | 10 | 273 mm |
| 12 | 318.5 JIS | — | JIS 300 A | — | — |
| | 323.9 mm | DN 300 | — | 12 | 323.9 mm |
| 14 | 355.6 mm | DN 350 | JIS 350 A | 14 | 355.6 mm |
| | 377 mm China | — | — | — | 377 mm |
| 16 | 406.4 mm | DN 400 | JIS 400 A | 16 | 406.4 mm |
| | 426 mm China | — | — | — | 426 mm |
| 18 | 457.2 mm | DN 450 | JIS 450 A | 18 | 457.2 mm |
| | 480 mm China | — | — | — | 480 mm |
| 20 | 508 mm | DN 500 | JIS 500 A | 20 | 508 mm |
| | 530 mm China | — | — | — | 530 mm |
| 22 | 558.8 mm | — | JIS 550 A | 22 | 559 mm |
| 24 | 610 mm | DN 600 | JIS 600 A | 24 | 610 mm |
| | 630 mm China | — | — | — | 630 mm |
| 26 | 660 mm | — | JIS 650 A | 26 | 660 mm |
| 28 | 711 mm | DN 700 | — | 28 | 711 mm |
| 30 | 762 mm | — | — | 30 | 762 mm |
| 32 | 813 mm | DN 800 | — | 32 | 813 mm |
| 34 | 864 mm | — | — | 34 | 864 mm |
| 36 | 914 mm | DN 900 | — | 36 | 914 mm |
| 40 | 1016 mm | DN 1000 | — | 40 | 1016 mm |
| 42 | 1067 mm | DN 1050 | — | 42 | 1067 mm |
| 44 | 1118 mm | DN 1100 | — | 44 | 1118 mm |
| 46 | 1168 mm | DN 1150 | — | 46 | 1168 mm |
| 48 | 1219 mm | DN 1200 | — | 48 | 1219 mm |