

Redukční spojka S 750

Skutečný rozměr (mm)	Maximální provozní tlak (kPa)	Max. Koncové zatížení. [N]	Vzdálenost mezi potrubím [mm]	Úhlová odchylka		Počet-rozměr šroub/matice (mm)	Rozměr spojky (mm)			Přibližná váha (kg/ks)
				Stupně pro spojku	Potrubí [mm/m]		X	Y	Z	
60.3 X 33.7	2.410	4.450	0 - 1.8	0° - 57'	17	2 - M10 X 51	86	127	48	0.9
60.3 X 48.3	2.410	4.450	0 - 1.8	0° - 57'	17	2 - M10 X 51	86	127	48	1.0
73.0 X 60.3	2.410	6.900	0 - 1.8	0° - 47'	14	2 - M10 X 51	105	149	48	1.4
76.1 X 60.3	2.410	6.900	0 - 1.8	0° - 47'	14	2 - M10 X 51	105	149	48	1.4
88.9 X 60.3	2.410	6.900	0 - 1.8	0° - 39'	11	2 - M12 X 70	121	171	48	2.1
88.9 X 73.0	2.410	10.125	0 - 1.8	0° - 39'	11	2 - M12 X 70	121	171	48	1.9
88.9 X 76.1	2.410	10.125	0 - 1.8	0° - 39'	11	2 - M12 X 70	121	171	48	1.9
114.3 X 60.3	2.410	6.900	0 - 1.8	1° - 19'	25	2 - M16 X 83	156	216	56	4.0
114.3 X 73.0	2.410	10.125	0 - 3.2	1° - 19'	25	2 - M16 X 83	156	216	56	3.8
114.3 X 76.1	2.410	10.125	0 - 3.2	1° - 19'	25	2 - M16 X 83	156	216	56	3.8
114.3 X 88.9	2.410	14.975	0 - 3.2	1° - 19'	25	2 - M16 X 83	156	216	56	3.0
141.3 X 114.3	2.410	24.765	0 - 3.2	1° - 3'	19	2 - M20 X 108	181	251	54	4.9
165.1 X 114.3	2.410	24.765	0 - 3.2	0° - 55'	16	2 - M20 X 108	216	286	56	6.9
168.3 X 114.3	2.410	24.765	0 - 3.2	0° - 52'	15	2 - M20 X 108	216	286	57	7.5
168.3 X 141.3	2.410	37.825	0 - 3.2	0° - 52'	15	2 - M20 X 108	216	283	54	5.7
219.1 X 168.3	2.410	53.400	0 - 3.2	0° - 38'	11	2 - M22 X 127	273	356	60	10.1

